

## Conditions of Architectural Review Approval

### PLN25-00093 / 3000 BOWERS AVENUE

#### Architectural Review (PLN25-00093) for the Construction of an Approximately 145,000 Square Foot Industrial Building with Associated Site Improvements including a Surface Parking Lot and Landscaping

#### GENERAL / PERFORMANCE

- G1. **Permit Expiration.** This Permit shall automatically be revoked and terminated if not used within **two years** of original grant or within the period of any authorized extensions thereof. The date of granting of this Permit is the date this Permit is approved by the decision-making body and the appeal period has been exhausted. The expiration date is April 16, 2026.
- G2. **Conformance with Plans.** Prior to the issuance of Building Permit, the development of the site and all associate improvements shall substantially conform to the approved plans on file with the Community Development Department, Planning Division. No change to the plans will be made without prior review by the Planning Division through approval of a Minor Amendment or through an Architectural Review, at the discretion of the Director of Community Development or designee. Each change shall be identified and justified in writing.
- G3. **Conditions on Plans.** All conditions of approval for this Permit shall be reprinted and included within the first three sheets of the building permit plan sets submitted for review and approval. At all times these conditions of approval shall be on all grading and construction plans kept on the project site.
- G4. **Necessary Relocation of Public Facility.** If relocation of an existing public facility becomes necessary due to a conflict with the owner or designee's new improvements, then the cost of said relocation shall be borne by the owner.
- G5. **Indemnify and Hold Harmless.** The owner or designee agrees to defend and indemnify and hold City, its officers, agents, employees, officials and representatives free and harmless from and against any and all claims, losses, damages, attorney's fees, injuries, costs, and liabilities from any suit for damages or for equitable or injunctive relief which is filed by a third party against the City by reason of its approval of owner or designee's project.
- G6. **Code Compliance.** The construction permit application drawings submitted to the Santa Clara Building Division shall include an overall California Building Code analysis; proposed use and occupancy of all spaces (CBC Ch. 3), all building heights and areas (CBC Ch. 5), all proposed types of construction (CBC Ch. 6), all proposed fire and smoke protection features, including all types of all fire rated penetrations proposed (CBC Ch. 7), all proposed interior finishes fire resistance (CBC Ch. 8), all fire protection systems proposed (CBC Ch. 9), and all means of egress proposed (CBC Ch. 10). Noncombustable exterior wall, floor, and roof finishes are strongly encouraged.

- a. During construction retaining a single company to install all fire related penetrations is highly recommended.
  - b. The grade level lobbies shall be minimum 1-hour rated all sides and above.
  - c. All stair shafts shall be minimum 1-hour rated.
  - d. All elevator shafts shall be minimum 1-hour rated.
  - e. All trash chute shafts shall be minimum 1-hour rated.
  - f. Recommendation: provide minimum two trash chutes; one for recyclables, one for trash, each trash chute to be routed down to a grade level trash collection room.
  - g. Any trash rooms shall be minimum 1-hour rated all sides and above.
- G7. **Building Codes as Amended.** See Title 15 of the Santa Clara City Code for any amendments to the California Building Codes.
- G8. **Reach Codes.** This project is subject to the provisions of the City of Santa Clara 2022 Reach Code, effective January 2022. See Ordinance No. 2034 and/or Title 15 of the Santa Clara City Code.
- a. Chapter 15.36 – Energy Code for “all electric” provisions for new construction.
  - b. Chapter 15.38 – Green Building Code for additional Electric Vehicle Charging requirements for new construction.
- G9. Comply with all applicable codes, regulations, ordinances and resolutions.

## **COMMUNITY DEVELOPMENT - PLANNING DIVISION**

### **DESIGN / PERFORMANCE – PRIOR TO BUILDING PERMIT ISSUANCE**

- P1. **Roof Mounted Mechanical Equipment.** All roof mounted mechanical equipment shall be placed within a screened roof top enclosure depicted on the elevation drawings or located below the parapet level and shall not be visible from the ground at any distance from the building. Cross section roof drawings shall be provided at the building permit stage indicating the relative height of the screen wall or parapet. Minimum screen height or parapet depth shall be five feet or greater to match the height of any proposed equipment.
- P2. **Tree Replacement (on-site).** Trees permitted by the City for removal shall be replaced on-site at a ratio of 2:1 (24” box). (SCC 12.35.090)
- P3. **Construction Management Plan.** The owner or designee shall submit a construction management plan addressing impacts to the public during construction activities including: showing work hours, noticing of affected businesses, construction signage, noise control, storm water pollution prevention, job trailer location, contractor parking, parking enforcement, truck hauling routes, staging, concrete pours, crane lifts, scaffolding, materials storage, pedestrian safety, and traffic control. The plan shall be submitted to the Director of Community Development or designee for approval prior to issuance of demolition and building permits.

### **DURING CONSTRUCTION – PRIOR TO OCCUPANCY**

- P4. **Construction Hours.** Construction activity shall be limited to the hours of 7:00 a.m. to 6:00 p.m. weekdays and 9:00 a.m. to 6:00 p.m. Saturdays for projects within 300 feet of a residential use and shall not be allowed on recognized State and Federal holidays.

- P5. **Construction Trash/Debris.** During construction activities, the owner or designee is responsible for collection and pick-up of all trash and debris on-site and adjacent public right-of-way.
- P6. **Construction Parking.** Off street parking is required to be available from the time of issuance of building permits until the issuance of certificate of occupancy. 29 parking spaces shall be made available. Off-street construction parking lots are required to be maintained mud-free and dustless. If the off-street construction parking lot is located on an unpaved surface, daily street sweeping of surrounding streets is required. (SCC 18.38.030)
- P7. **Landscape Water Conservation.** The owner or designee shall ensure that landscaping installation meets City water conservation criteria in a manner acceptable to the Director of Community Development.

### **OPERATIONAL CONDITIONS**

- P8. **Landscaping Installation & Maintenance.** The owner or designee shall ensure that the landscaping installed and accepted with this project shall be maintained on the site as per the approved plans. Any alteration or modification to the landscaping shall not be permitted unless otherwise approved by the Director of Community Development.
- P9. **Transportation Demand Management (TDM) Program (Non-Residential project)** The Owner or designee shall implement the project TDM program that includes elements to reduce vehicle miles traveled (VMT) by 25 percent per the City's 2022 Climate Action Plan. A final TDM plan shall be submitted to the Director of Community Development or designee prior to Building Permit Final by the Planning Division. The property owner or designee shall monitor the project TDM program and submit an annual report to the Director of Community Development or designee. Monitoring and reporting requirements may be revised in the future if the minimum reduction is not achieved through the measures and programs initially implemented.

### **MITIGATION MEASURES**

- P10. **Mitigation Monitoring and Reporting Program.** Mitigation Monitoring and Reporting Program (MMRP), prepared for this project in compliance with the California Environmental Quality Act (CEQA), shall be incorporated by reference as conditions of approval. The applicant shall comply with all specified mitigation measures in the timelines outlined in the project's MMRP.
- P11. **Environmental Conditions.**
- a. Construction Particulate Matter and Dust Emissions (Best Management Practices):
    - i. All exposed surfaces (e.g., parking areas, staging areas, soil piles, graded areas, and unpaved access roads) shall be watered two times per day.

- ii. All haul trucks transporting soil, sand, or other loose material off-site shall be covered.
  - iii. All visible mud or dirt track-out onto adjacent public roads shall be removed using wet power vacuum street sweepers at least once per day. The use of dry power sweeping is prohibited.
  - iv. All vehicle speeds on unpaved roads shall be limited to 15 miles per hour (mph).
  - v. All roadways, driveways, and sidewalks to be paved shall be completed as soon as possible. Building pads shall be laid as soon as possible after grading unless seeding or soil binders are used.
  - vi. Replant vegetation in disturbed areas as soon as possible after completion of construction.
  - vii. Idling times shall be minimized either by shutting equipment off when not in use or reducing the maximum idling time to 5 minutes (as required by the California airborne toxics control measure Title 13, Section 2485 of the California Code of Regulations [CCR]). Clear signage shall be provided for construction workers at all access points.
  - viii. All construction equipment shall be maintained and properly tuned in accordance with manufacturer's specifications. All equipment shall be checked by a certified mechanic and determined to be running in proper condition prior to operation.
  - ix. Post a publicly visible sign with the telephone number of the on-site project superintendent to contact regarding dust complaints. This person shall respond and take corrective action within 48 hours. The Air District's phone number shall also be visible to ensure compliance with applicable regulations.
- b. Construction Water Quality Impacts (Best Management Practices):
- i. Burlap bags filled with drain rock shall be installed around storm drains to route sediment and other debris away from the drains.
  - ii. Earthmoving or other dust-producing activities shall be suspended during periods of high winds.
  - iii. All exposed or disturbed soil surfaces shall be watered at least twice daily to control dust, as necessary.
  - iv. Stockpiles of soil or other materials that can be blown by the wind shall be watered or covered.
  - v. All trucks hauling soil, sand, and other loose materials shall be required to cover all trucks or maintain at least two feet of freeboard.
  - vi. All paved access roads, parking areas, and staging areas adjacent to the construction sites shall be swept daily (with water sweepers).
  - vii. Vegetation in disturbed areas shall be replanted as quickly as possible.
  - viii. All unpaved entrances to the site shall be filled with rock to knock mud from truck tires prior to entering City streets. A tire wash system may also be employed at the request of the City.
- c. Post-Construction Water Quality (Best Management Practices):

- i. When the construction phase is complete, a Notice of Termination (NOT) for the General Permit for Construction will be filed with the RWQCB and the City of Santa Clara. The NOT shall document that all elements of the SWPPP have been executed, construction materials and waste have been properly disposed of, and a post-construction stormwater management plan is in place as described in the SWPPP for the project site.
  - ii. All post-construction Treatment Control Measures (TCMs) shall be installed, operated, and maintained by qualified personnel. On-site inlets will be cleaned out at a minimum of once per year, prior to the wet season.
  - iii. The property owner/site manager shall keep a maintenance and inspection schedule and record to ensure the TCMs continue to operate effectively for the life of the project. Copies of the schedule and record must be provided to the City upon request and must be made available for inspection on-site at all times.
- d. Driver Sight Distance: As identified by the transportation analysis (dated August 14, 2025), all planting and structures within the sight triangle shall be less than 3 feet tall to guarantee outbound drivers at the Oakmead Village Court at the southside of the project site could see vehicles approaching on southbound Oakmead Village Court 200 feet away.

## **COMMUNITY DEVELOPMENT - BUILDING DIVISION**

### **DESIGN / PERFORMANCE – PRIOR TO BUILDING PERMIT ISSUANCE**

- BD1. **Addressing.** Prior to overall construction permit application, submit to the Santa Clara Building Division, 2 copies of an addressing diagram request, to be prepared by a licensed architect or engineer. The addressing diagram(s) shall include all proposed streets and all building floor plans. The addressing diagram(s) shall conform to Santa Clara City Manager Directive #5; Street Name and Building Number Changes, and Santa Clara Building Division Address Policy For Residential and Commercial Developments. The addressing diagram(s) shall indicate all unit numbers to be based off established streets, not alleys nor access-ways to garages. Allow a minimum of 10 working days for initial staff review. Please note city staff policy that existing site addresses typically are retired. Provide digital pdf printed from design software, not scanned from printed paper sheet.
- a. Any building or structure that is demolished shall have its address retired and a new address/s shall be issued for the project.
- BD2. **Flood Zone.** The construction permit application drawings submitted to the Santa Clara Building Division shall include a copy of the latest Federal Emergency Management Agency (FEMA) Flood Zone Map: <https://msc.fema.gov/portal/home>. The project drawings shall indicate how the project complies with the Santa Clara Flood Damage Prevention Code.
- a. FEMA Flood Zone map designations and requirements are based on the map in effect at date of Building Permit issuance.
- BD3. **Water Pollution Control.** The construction permit application drawings submitted to the Santa Clara Building Division shall include Santa Clara Valley Urban Runoff Pollution Prevention Program Low Impact Development (LID) practices [http://www.scvrppp-w2k.com/nd\\_wp.shtml](http://www.scvrppp-w2k.com/nd_wp.shtml). All projects that disturb more than one acre, or projects that are

part of a larger development that in total disturbs more than one acre, shall comply with the Santa Clara Valley Urban Runoff Pollution Prevention Program Best Management Practices (BMP): [http://www.scvurppp-w2k.com/construction\\_bmp.shtml](http://www.scvurppp-w2k.com/construction_bmp.shtml), and shall provide a Storm Water Pollution Prevention Plan (SWPPP) by a certified Qualified SWPPP Developer (QSD). All site drainage and grading permit applications submitted to the Santa Clara Building Division shall include a city of Santa Clara "C3" data form, available on this web page.

- a. <https://www.santaclaraca.gov/our-city/departments-g-z/public-works/environmental-programs/stormwater-pollution-prevention> and will be routed to a contract consultant for review

**BD4. Submittal Requirements.** The overall project construction permit application shall include the geotechnical, architectural, structural, energy, electrical, mechanical, and plumbing drawings and calculations. Prior to the issuance of the overall project construction permit, a conditions of approval review meeting must be held in city hall, which meeting must be attended by the on-site field superintendent(s). The meeting will not be held without the attendance of the on-site field superintendent(s). The on-site grading permit shall be a separate permit application to the Building Division

#### **DURING CONSTRUCTION – PRIOR TO OCCUPANCY**

**BD5. Temporary Certificates of Occupancy.** Temporary Certificates of Occupancy (TCO) will not be routinely issued and will be considered on a very limited basis only when there is a clear and compelling reason for city staff to consider a TCO. A TCO will be approved only after all applicable City staff have approved in writing; Planning, P.W./ Engineering, Fire Prev., Santa Clara Water, Silicon Valley Power, and any other applicable agencies such as the Santa Clara County Health Dept., with the Building Division being the final approval of all TCO.'s.

#### **COMMUNITY DEVELOPMENT – HOUSING DIVISION**

##### **DESIGN / PERFORMANCE – PRIOR TO BUILDING PERMIT ISSUANCE**

**H1. Impact Fee.** In accordance with the Santa Clara City Code chapter 17.40, this project is subject to the requirements of the Affordable Housing Ordinance which may be met through payment of an impact fee. The requirement may be satisfied by paying an impact fee based on the project's square footage.

Office (< 20,000 sf): The requirement may be satisfied through payment of an impact fee of \$15.24 per square foot. For office space greater than 20,000 sq. ft., the fee increases to \$30.48 per square foot.

Class A Warehouse (Light Industrial > 20,000 sf): The requirement may be satisfied through payment of an impact fee of \$15.24 per square foot.

Note: Impact fees must be paid prior to the issuance of the building's certificate of occupancy. All fees are based on the current Municipal Fee Schedule in effect at the time of project approval. If the proposed square footage changes at the time of building permit issuance, the impact fee will be adjusted accordingly.

Estimated Fees Based on Proposed Project

Office (1st Floor): 8,000 sq. ft.

Office (2nd Floor): 8,000 sq. ft.

Warehouse: 128,579 sq. ft.

Total Area: 144,579 sq. ft.

Calculation: 144,579 sq. ft. x \$15.24/sq. ft. = \$2,203,383.96 (estimated fee)

- H2. Please note that the impact fee provided here is an estimate and may change if the proposed square footage changes. The Applicant shall pay impact fees prior to the issuance of the occupancy certificate of the building (all fees are based on the current Municipal Fee Schedule in effect at the time the project is approved).

**FIRE DEPARTMENT**

**DESIGN / PERFORMANCE – PRIOR TO BUILDING PERMIT ISSUANCE**

- F1. **Hazmat Clearance.** Prior to any Building Permit issuance, Hazardous Materials Closure (HMCP) is required as applicable: This is a permit issued by the Santa Clara Fire Department, Community Risk Reduction Division. Hazardous materials closure plans are required for businesses that used, handled or stored hazardous materials. While required prior to closing a business this is not always done by the business owner and therefore should be part of the developer's due diligence. The hazardous materials closure plans demonstrate that hazardous materials which were stored, dispensed, handled or used in the facility/business are safely transported, disposed of or reused in a manner that eliminates any threat to public health and environment.

As of March 27, 2026 – it is noted that there are no remaining structures at the property. Last visit, there were no visible aboveground tanks or drums at the site. Prior to issuance, the project to verify that all required closure permits have been properly finalized.

- F2. **Hazmat Clearance.** Prior to any Building Permit Issuance, a Phase II environmental assessment is required to be submitted to CRRD for review. If hazards are present that require site mitigation, cleanup, or management of chemical contaminants in soil, soil vapor, or groundwater a separate permit from one of the regulatory agencies below will be required. The type and extent of contamination on site(s) will govern which of the regulatory agencies noted below can supervise the cleanup: Department of Toxic Substances Control (DTSC); State Water Resources Control Board; or Santa Clara County, Department of Environmental Health.

If the project intends to contract with a State or County Agency for onsite/offsite environmental remediation activities the following documentation shall be provided to the Fire Department Community Risk Reduction Division prior to issuance of a Building Permit for demolition or grading: Oversight agency case number; and Oversight managers contact name, phone number.

As of March 27, 2026 – A Phase II ESA, dated November 10, 2025, was submitted to the City under the Building Permit BLD25-04422. Based on the results noted in the Phase II ESA, there are some areas of known contamination. The project has communicated to

the City they are in the process of working with the County of Santa Clara as their oversight cleanup agency.

Upon establishment of the case, please submit case number, case lead, and approved site/soil management plan for the site. This will be an integrated condition on the grading permit.

Additionally, since the County has not completed its assessment of the site data, there could be other conditions set forth from the County that may be integrated and integral in the City's respective permits.

- F3. **Fire Flow Requirement.** Prior to Building Permit Issuance, provide documentation from the City of Santa Clara Water & Sewer Department that the minimum required fire-flow can be met. Fire Department fire-flow will be based on the current California Fire Code. The most restrictive departments requirement shall apply.
- F4. **Fire Hydrants.** Prior to Building Permit Issuance, building plans shall show the required number, location and distribution of fire hydrants for the buildings will be based on the current California Fire Code, Appendix C as amended. The required number of fire hydrants will be based on the fire-flow before the reduction for fire sprinklers. Both public and private fire hydrants may be required.
- F5. **Fire Department Access.** Prior to Building Permit Issuance, a five-foot all-weather perimeter pathway around the entire perimeter of the buildings to facilitate firefighter access is required to be incorporated into the Building permit submittal.
- F6. **Fire Department Access.** Prior to the issuance of the Building Permit, approval for fire department apparatus access roads is required. Roadways must be provided to comply with all the following requirements:
  - a. Fire apparatus access roadways shall be provided so that the exterior walls of the first story of the buildings are located not more than 150 feet from fire apparatus access as measured by an approved route around the exterior of each building. In addition, aerial apparatus roadways must be located so aerial apparatus will have clear access to the "entire" face/sides of the building. The minimum number of sides is project-specific and depends on the building configuration, building design, occupancy, and construction type, etc. As part of Building Permit Issuance, an alternative materials, design, and methods of construction and equipment permit application will need to be submitted for review and approval incorporating applicable mitigation measures as determined by the fire department for the lack of compliance. Please note acceptable mitigation methods may have been discussed during the planning stage. Those mitigations are not guaranteed until a formal alternate means permit is submitted concurrently with the Building Plans. Conversely, an acceptable mitigation method may not have been discussed and will be evaluated under an alternate means permit at the building permit stage.
  - b. Where required for high-piled storage, fire department access doors shall be provided at a maximum spacing of 125 linear feet, measured center to center. Depending on the commodity classification, storage arrangement, and storage area, the fire apparatus access roadways shown on the plans may be required to extend around the entire building perimeter, regardless of AM&M.
  - c. The "minimum" unobstructed vertical clearance shall not be less than 13 feet 6 inches.

- d. The “minimum” width of aerial roadways for aerial apparatus is 26 feet.
  - e. The minimum inside turning radius shall be 30 feet.
  - f. The “minimum” width of roadways for aerial apparatus is 26 feet. Aerial access roadways shall be located a minimum of 15 feet and a maximum of 30 feet from the protected building. This requirement is only applicable when Appendix D of the Fire Code is enforceable.
  - g. Overhead utility and power lines easements shall not be located over fire apparatus access roads or between the aerial fire apparatus roads and the buildings to avoid the possibility of injury and equipment damage from electrical hazards.
  - h. Fire apparatus access roadways shall be all-weather surface(s) designed to support a gross vehicle weight of 75,000-pounds.
  - i. Trees at full development must not exceed 30 feet in height and not impair aerials apparatus operations to sweep opposing sides of a building. Other obstructions such as site lighting, bio-retention, and architectural features are reviewed case-by-case to ensure they do not obstruct aerial and ground ladder access.
  - j. Traffic control/calming devices are not permitted on any designated fire access roadway unless approved. A separate Fire Department permit is required for any barrier devices installed along fire department apparatus access roads.
  - k. Prior to any Building Department Issuance, all fire department apparatus access roadways on private property are required to “be recorded” with the County of Santa Clara as Emergency Vehicle Access Easements (EVAE’s) and reviewed by the Fire Department. No other instruments will be considered as substitutions such as P.U.E, Ingress/Egress easements and/or City Right-of-Ways.
- F7. **Fire Department Access.** Prior to the start of construction, roadways and water supplies for fire protection are required to be installed and made serviceable and maintained throughout the course of construction.
- F8. **Fire Department Access.** Prior to issuance of the Building Permit, a gate permit is required to be obtained. Openings for access gates located across fire apparatus access roads shall be a minimum of 20 feet of clear width. Gates shall also be provided with a minimum unobstructed vertical clearance of 16-feet. All gates installed on designated fire department access roads must be electrically automatic powered gates. Gates shall be provided with an emergency power or be of a fail-safe design, allowing the gate to be pushed open without the use of special knowledge or equipment. A Tomar Strobe Switch or 3M Opticom detector shall be installed to control the automatic gate(s) to allow emergency vehicles (e.g., fire, police, ems). Said device shall be mounted at a minimum height of eight to ten feet (8’ - 10’) above grade.
- F9. **Emergency Responder Radio Coverage System.** Prior to Building Permit Issuance, provisions shall be made for Emergency Responder Radio Coverage System (ERRCS) equipment, including but not limited to pathway survivability in accordance with Santa Clara Emergency Responder Radio Coverage System Standard.
- F10. **Alternative Means and Methods.** Prior to any Building Permit issuance, an alternate means or methods permits to mitigate any code deficiency must be submitted and approved. Please submit this permit concurrently with the building plans. Please note specific mitigations may have been discussed during the planning process. None of these discussions are binding and can only be formally approved through submitting an AMMR permit. The AMMR permit is formally documenting that and still needs to be submitted.

- F11. **Hazmat Information.** Prior to Building Permit Issuance, a Hazardous Materials Inventory Statement including refrigerants is required to be submitted and reviewed with the Building Permit if applicable.
- F12. **Fire Safety During Construction.** Prior to Building Permit Issuance, a permit for Construction Safety & Demolition shall be submitted to the fire department for review and approval in compliance with our Construction Safety & Demolition standard.

#### **DURING CONSTRUCTION – PRIOR TO OCCUPANCY**

- F13. **Shared Fire Protection Features that Cross Property Lines.** Prior to Building Permit Final, any EVAEs or fire protection equipment (including but not limited to fire service undergrounds, sprinkler piping, fire alarm equipment, fire pumps, ERRCS) that cross property lines or is not located on the parcel of the building it serves shall have a CC&R legally recorded detailing who is responsible for maintenance and repair of the EVAE or fire protection equipment.
- F14. **Fire Protection Systems Before Occupancy.** Prior to any Certificate of Occupancy Issuance (temporary or permanent), fire-life safety systems installations must be fully installed, functional, and approved.

#### **PUBLIC WORKS DEPARTMENT - ENGINEERING**

##### **DESIGN / PERFORMANCE – PRIOR TO BUILDING PERMIT ISSUANCE**

- E1. **Site Clearance.** Obtain site clearance through Public Works Department prior to issuance of Building Permit. Site clearance will require payment of applicable development fees. Other requirements may be identified for compliance during the site clearance process. Contact Public Works Department at (408) 615-3000 for further information.
- E2. **Easement.** Obtain Council approval of a resolution ordering vacation of existing public easement(s) proposed to be abandoned, if any, through Public Works Department, and pay all appropriate fees, prior to start of construction.
- E3. **Design.** The sanitary sewer (SS) discharge information (i.e., building use, square footage, point of connection to the public system, 24-hour average and peak SS flow graphs for the peak day showing average daily and peak daily SS flows, full day diurnal curve for peak summer and winter days, and extreme weather discharge with frequency of extreme weather event) submitted by the developer was added to the City's Sanitary Sewer Hydraulic Model (SSHM) to determine if there is enough SS conveyance capacity in the SS trunk system to accommodate the proposed development. The SSHM output indicates that there should be enough SS conveyance capacity to accommodate the proposed development. The SSHM output may change based on pending development applications and future projects. The SSHM output does not guarantee or in any way reserve or hold SS conveyance capacity until developer has Final Approval for the project. For purposes of this condition, "Final Approval" shall mean the final vote of the City Council necessary for all entitlements to be approved, unless a legal challenge is brought to the Council decisions, in which case the Final Approval shall mean the final disposition of the legal challenge.

##### **DURING CONSTRUCTION – PRIOR TO OCCUPANCY**

- E4. **Encroachment Permit.** All work within the public right-of-way and/or public easement, which is to be performed by the Developer/Owner, the general contractor, and all

- subcontractors shall be submitted within a Single Encroachment Permit to be reviewed and issued by the City Public Works Department. Issuance of the Encroachment Permit and payment of all appropriate fees shall be completed prior to commencement of work, and all work under the permit shall be completed prior to issuance of occupancy permit.
- E5. **Encroachment Permit.** Submit public improvement/encroachment permit plans prepared in accordance with City Public Works Department procedures which provide for the installation of public improvements directly to the Public Works Department. Plans shall be prepared by a Registered Civil Engineer and approved by the City Engineer prior to approval and recordation of final map and/or issuance of building permits.
- E6. **Encroachment Permit.** All work within Santa Clara County right-of-way shall require a Santa Clara County encroachment permit.
- E7. **Encroachment Permit.** Existing non-standard or non-ADA compliant frontage improvements shall be replaced with current City standard frontage improvements as directed by the City Engineer or his designee.
- E8. **Encroachment Permit.** Damaged curb, gutter, and sidewalk within the public right-of-way along property's frontage shall be repaired or replaced (to the nearest score mark) in a manner acceptable to the City Engineer or his designee. The extents of said repair or replacement within the property frontage shall be at the discretion of the City Engineer or his designee.
- E9. **Encroachment Permit.** Owner or designee shall provide a complete storm drain study for the 10-year and 100-year storm events. The grading plans shall include the overland release for the 100-year storm event and any localized flooding areas. System improvements, if needed, will be at developer's expense.
- E10. **Encroachment Permit.** Sanitary sewer and storm drain mains and laterals shall be outside the drip line of mature trees or ten (10) feet clear of the tree trunk, whichever is greater, to the satisfaction of the City Engineer.
- E11. **Encroachment Permit.** Provide root barriers when the drip line of the mature trees covers the sidewalk. Root barriers for sidewalk protection shall be 16' long or extend to drip line of the mature tree, whichever is greater, and be 1.5' deep, and centered on trees. Root barriers for curb and gutter protection shall be 16' long or extend to drip line of the mature tree, whichever is greater, and be 2' deep, and centered on trees.
- E12. **Encroachment Permit.** Existing streetlights shall be clear of proposed sidewalk, developer shall relocate as necessary.
- E13. **Encroachment Permit.** Pavement treatment shall be full street reconstruction for the full street width of Oakmead Village Court along the project frontage. The thickness of the asphalt concrete replacement shall be the existing asphalt concrete thickness determined by potholing or City equivalent structural pavement section thickness with a TI value of 6, whichever is thicker.
- E14. **Encroachment Permit.** Pavement treatment shall be slurry seal with digouts for the half street width (from curb to median island) of Bowers Avenue along the project frontage.
- E15. **Easement.** Dedicate required on-site easements for any new public utilities, and/or emergency vehicle access by means of subdivision map or approved instrument at time of development.
- E16. **Easement.** Dedicate sidewalk easements along the project frontage where public sidewalks extend into private property. Sidewalk easements are to be 1' behind proposed back of walk where there is landscaping behind sidewalk. Sidewalk easement where

hardscape is behind sidewalk is to be at back-of-walk. Cold joint is required between public sidewalk and private hardscape.

- E17. **Agreement.** If requested, owner or designee shall prepare and submit for City approval a maintenance plan for all sidewalk, curb and gutter, landscaping and irrigation system improvements installed within the public right-of-way prior to encroachment permit issuance. Such plan shall include at a minimum, maintenance requirements for trees and shrubs, in acknowledgement of developer's/property owner's obligation under Chapter 12.30 and 17.15.

## **PUBLIC WORKS DEPARTMENT – STORMWATER**

### **DESIGN / PERFORMANCE—PRIOR TO BUILDING PERMIT ISSUANCE**

- ST1. **Final Stormwater Management Plan.** Prior to City's issuance of Building or Grading Permits, the applicant shall develop a Final Stormwater Management Plan, update the C.3 Data Form, the Special Project Narratives and Worksheet (as appropriate), and an Erosion and Sediment Control Plan.
- ST2. **3<sup>rd</sup> Party Review of Final Stormwater Management Plan.** The Final Stormwater Management Plan and all associated calculations shall be reviewed and certified by a qualified 3<sup>rd</sup> party consultant from the SCVURPPP List of Qualified Consultants, and a 3<sup>rd</sup> party review letter (on design) shall be submitted with the Plan.
- ST3. **Notice of Intent.** For project that disturbs a land area of one acre or more, the applicant shall provide a copy of the Notice of Intent (NOI) with WDID number for coverage under the State Construction General Permit. Active projects with NOI will be inspected by the City once per month during the wet season (October – April).
- ST4. **Best Management Practices.** The applicant shall incorporate Best Management Practices (BMPs) into construction plans and incorporate post-construction water runoff measures into project plans. Include the SCVURPPP Countywide Construction BMPs Plan Sheet with the plans. Applicant to add Source control measures with designations from C.3 stormwater handbook, Appendix H.
- ST5. **C.3 Treatment Facilities Construction Notes.** Include the C.3 Treatment Facilities Construction Notes on the Improvement Plans and/or Stormwater Control Plans.
- ST6. **Decorative & Recreational Water Features.** Decorative and recreational water features such as fountains, pools, and ponds shall be designed and constructed to drain to the sanitary sewer system only.
- ST7. **Small Projects.** For single-family homes and other small projects that create and/or replace 2,500 – 10,000 square feet of impervious surface area, the applicant shall implement at least one of the following site design measures:
- a. Direction of roof runoff into cisterns or rain barrels
  - b. Direction of roof, sidewalk, walkway, patio, driveway, or parking lot runoff onto vegetated areas
  - c. Construction of sidewalks, walkways, patios, bike lanes, driveways, and parking lots with permeable surfaces
- Plans shall specify which site design measures are selected for the project and show the direction of flow from impervious surfaces to the selected site design measures. All measures shall meet the design criteria in the 2016 C.3. Stormwater Handbook, Appendix K: Standard Specifications for Lot-Scale Measures for Small Projects.
- ST8. **Interior Floor Drains.** Interior floor drains shall be plumbed to the sanitary sewer system and not connected to the City's storm drain system.

- ST9. **Trash Enclosure Floor Drains.** Floor drains within trash enclosures shall be plumbed to the sanitary sewer system and not connected to the City's storm drain system.
- ST10. **Architectural Copper.** The use of architectural copper is prohibited.

#### **DURING CONSTRUCTION OR OPERATION**

- ST11. **Biotreatment Soil Media.** Applicant shall install biotreatment soil media that meets the minimum specifications as set forth in the SCVURPPP C.3 Stormwater Handbook. If percolation rate test of the biotreatment soil mix is not performed on-site, a certification letter from the supplier verifying that the soil meets the specified mix (the date of such document shall not be older than 3 months).
- ST12. **Stormwater Control Measure Inspection.** At critical construction phases, all stormwater control measures shall be inspected for conformance to approved plans by a qualified 3<sup>rd</sup> party consultant from the SCVURPPP List of Qualified Consultants.
- ST13. **Inspections.** Permeable Pavement, Media Filter vaults, and Trash Full Capture Devices shall be inspected by a 3<sup>rd</sup> party reviewer and/or manufacturer representative for conformance with the details and specifications of the approved plans. All new pervious concrete and porous asphalt pavements should have a minimum surface infiltration rate of 100 in./hr. as described in the SCVURPPP C.3 Handbook. A map displaying the number, location and details of full trash capture devices shall be prepared as an attachment to the Operations and Maintenance (O&M) Agreement with the City.
- ST14. **Stormwater Treatment Facilities.** Stormwater treatment facilities must be designed, installed, and maintained to achieve the site design measures throughout their life in accordance to the SCVURPPP C.3 Stormwater Handbook (Chapter 6 and Appendix C).
- ST15. **Amendments to Operation & Maintenance Agreement.** Any site design measures used to reduce the size of stormwater treatment measures shall not be installed for the project without the written approval from the City, installing the corresponding resizing of other stormwater treatment measures and an amendment of the property's O&M Agreement.
- ST16. **Stormwater Pollution Prevention Messaging.** Developer shall install an appropriate stormwater pollution prevention message such as "No Dumping – Flows to Bay" on any storm drains located on private property.
- ST17. **Outdoor Storage Areas.** All outdoor equipment and materials storage areas shall be covered and/or bermed, or otherwise designed to limit the potential for runoff to contact pollutants.

#### **PRIOR TO FINAL OF BUILDING PERMIT**

- ST18. **As-Built Drawings.** As-Built drawing shall be submitted to the Public Works Department.
- ST19. **3<sup>rd</sup> Party Concurrence Letter.** 3<sup>rd</sup> Party concurrence letter on the C.3 facilities construction shall be submitted to the Public Works Department. The letter shall be prepared by a 3<sup>rd</sup> party consultant from the SCVURPPP List of Qualified Consultants. The City reserves the right to review the 3<sup>rd</sup> party inspection report on the C.3 stormwater facility installation.
- ST20. **Final C.3 Inspection.** Applicant shall schedule and City shall conduct a final C.3 inspection.
- Operation & Maintenance Agreement.** The property owner shall enter into an Operation and Maintenance (O&M) Agreement with the City for all installed stormwater treatment measures and full trash capture devices in perpetuity. Applicants should contact Public Works Dept. - Environmental Services at (408) 615-3080 or [Street@SantaClaraCA.gov](mailto:Street@SantaClaraCA.gov) for assistance completing the Agreement. For more information and to download the most

recent version of the O&M Agreement, visit the City's stormwater resources website at <http://santaclaraca.gov/stormwater>. Inspection of permeable pavement, media filter vaults and full trash capture devices is to be done annually by December 31 of each year.

## **PUBLIC WORKS DEPARTMENT – TRANSPORTATION**

### **DESIGN—PRIOR TO BUILDING PERMIT ISSUANCE**

TR1. **Site Clearance.** Project shall implement any traffic improvements identified in the transportation analysis as prepared by Hexagon Transportation Consultants (dated August 14, 2025) for David J. Powers & Associates, Inc.

### **DURING CONSTRUCTION**

TR2. **Encroachment Permit.** Traffic improvements must comply with the City of Santa Clara Standard Details and Specifications for Public Works Construction.

TR3. **Encroachment Permit.** Visual obstructions over three feet in height will not be allowed within the driver's sight triangle near driveways in order to allow an unobstructed view of oncoming traffic.

TR4. **Encroachment Permit.** Project shall implement any traffic improvements or pay fair shares identified in the traffic analysis.

TR5. **Encroachment Permit.** Project shall implement mitigation measures identified in the VMT analysis.

TR6. **Encroachment Permit.** Protect in place all street signs and curb markings along the property frontage.

TR7. **Encroachment Permit.** All proposed driveways shall be ADA compliant per City Standard ST- 9.

TR8. **Encroachment Permit.** Santa Clara County permit will be required for all work within the right-of-way along Central Expressway.

TR9. **Encroachment Permit.** Conduct lighting analysis/evaluation for the proposed path and along Central Expressway project frontage per Section 4 of the Caltrans Traffic Operations Manual, Chapter 205-Lighting and Sign Illumination Systems, Part 1-Roadway Lighting (January 2025) to ensure nighttime visibility and discourage unsafe crossings toward Central Expressway. Improvements will be required should the lighting levels not be met based on the conducted lighting analysis.

TR10. **Encroachment Permit.** Install two (2) ADA compliant curb ramps along Oakmead Village Court to align with the existing ADA curb ramps on Oakmead Village Drive at the intersection of Oakmead Village Drive and Oakmead Village Court.

TR11. **Encroachment Permit.** For pedestrian safety and improve traffic operations, applicant shall install yield control on Oakmead Village Drive and appropriate CA MUTCD roadway yield markings where it intersects with Oakmead Village Court and a crosswalk crossing Oakmead Village Drive designed per City Standard TR-8.

TR12. **Encroachment Permit.** Update existing curb ramps at the pork-chop island at southwest corner of Central Expressway and Bowers Avenue and install ADA compliant curb ramps. Applicant shall discuss any additional modifications for the intersection of Central Expressway and Bowers Avenue with the County of Santa Clara. Please contact Ben Aghegnehu at [ben.aghegnehu@rda.sccgov.org](mailto:ben.aghegnehu@rda.sccgov.org) that can provide you any more details related to any roadwork within County right-of-way.

TR13. **Encroachment Permit.** Square off the southwest corner of Central/Bowers intersection.

- TR14. **Encroachment Permit.** Provide 5' wide minimum sidewalk along Oakmead Village Court and Central Expressway property frontages.
- TR15. **Encroachment Permit.** Unused driveways in the public right-of-way shall be replaced with City standard curb, gutter, and sidewalk per City Standard Detail ST-12.
- TR16. **Encroachment Permit.** Install a conduit connection between the County signal cabinet on the southwest corner of Bowers/Central Expwy intersection and the City of Santa Clara signal cabinet on the southwest corner of Bowers & Walsh/Kifer to allow for better coordination between the two traffic signals.”
- TR17. **Encroachment Permit.** Install sign at driveway just to the north of the Oakmead Village Drive/Oakmead Village Court intersection which states “Trucks only.”
- TR18. **Agreement.** Landscaping withing County ROW will require maintenance agreement.
- TR19. **Building Permit.** Class I and Class II bike parking shall be provided per the Updated City Zoning Code. Class I and Class II bicycle parking shall be conveniently accessible from the street, within 200 feet of a building entrance and/or highly visible areas.
- TR20. **Building Permit.** Trash collection shall be conducted on-site.
- TR21. **Building Permit.** On-street parking shall not be counted toward on-site parking requirements.
- TR22. **Building Permit.** Provide pedestrian ADA walkways from proposed buildings to public sidewalk.

## **PUBLIC WORKS DEPARTMENT – STREETS DIVISION**

### Right of Way Landscape

#### **DESIGN / PERFORMANCE – PRIOR TO BUILDING PERMIT ISSUANCE**

- L1. **Tree Preservations Specifications.** Include [City of Santa Clara Tree Preservation/City Arborist specifications](#) on all improvement plans.
- L2. **Mature Trees.** Identify existing mature trees to be maintained. Prepare a tree protection plans for review and approval by the City prior to any demolition, grading or other earthwork in the vicinity of existing trees on the site.
- L3. **Tree Replacement.** 2:1 tree replacement ratio required for all trees removed from the right-of-way.

#### **DURING CONSTRUCTION OR OPERATION**

- L4. **No Public Root Cutting.** No cutting of any part of **public**, including roots, shall be done without securing prior approval of the City Arborist. Tree trimming/removal shall be done in accordance to the City of Santa Clara Tree Preservation/City Arborist specifications and with direct supervision of a certified arborist (Certification of International Society of Arboriculture).

#### **PRIOR TO FINAL OF BUILDING PERMIT**

- L5. **In Lieu Fee.** If 2:1 replacement ratio cannot be met for removal of right of way landscape trees, tree planting fee must be paid prior to building permit final.

### Solid Waste

#### **DESIGN / PERFORMANCE – PRIOR TO BUILDING PERMIT ISSUANCE**

- SW1. **Post-Construction Solid Waste Generation Estimation and Collection Form.** The applicant shall complete and provide the Post-Construction Solid Waste Generation Estimation and Collection Form, which includes the estimation of trash and recycling materials generated from the project. Use the City's Solid Waste Guidelines for New and Redevelopment Projects as specified by the development type. Contact the Public Works Department at [Environment@SantaClaraCA.gov](mailto:Environment@SantaClaraCA.gov) or (408) 615-3080 for more information.
- SW2. **Site Plan.** The applicant shall provide a site plan showing all proposed locations of solid waste containers, chutes, compactors, trash enclosures and trash staging areas. The site plan shall show the route or access for trash and recycling collectors (trucks) including vertical clearance, turning radius and street/alley widths. All plans shall comply with the City's Solid Waste Guidelines. Solid metal roof, gates and a trench drain shall be installed within the trash enclosure and connected to the on-site sewer system.
- SW3. **Construction Waste Diversion.** For projects that involve construction, demolition or renovation of 5,000 square feet or more, the applicant shall comply with City Code Section 8.25.285 and recycle or divert at least sixty five percent (65%) of materials generated for discard by the project during demolition and construction activities. No building, demolition, or site development permit shall be issued unless and until applicant has submitted a construction and demolition debris materials check-off list. Applicant shall create a Waste Management Plan and submit, for approval, a Construction and Demolition Debris Recycling Report through the City's online tracking tool at <http://santaclara.wastetracking.com/>.
- SW4. **Authorized Service Haulers.** This project is subject to the City's Accumulation, Transportation and Disposal of Solid Waste Ordinance (Chapter 8.25 of the Municipal Codes), which requires the handling and disposal of waste by authorized service haulers. Insert the General Notes for the Construction & Demolition (C&D) Waste Management into construction plans in accordance with the City's municipal codes prior to the issuance of a Building or Grading permit. Provide the Green Halo waste online tracking number to Building staff prior to the issuance of a demolition or building permit.
- SW5. **Exclusive Franchise Hauling Area.** Project applicant shall contact the Public Works Department, Street Maintenance Division at (408) 615-3080 to verify if the property falls within the City's exclusive franchise hauling area. If so, the applicant is required to use the City's exclusive franchise hauler and rate structure for any hired debris boxes. Prior to the issuance of a Public Works clearance, the project applicant shall complete and sign the Construction and Demolition (C&D) / Waste Management Rules and Regulations Form.

#### **DURING CONSTRUCTION OR OPERATION**

- SW6. **Waste Generation Tracking.** Applicant to track all waste generated and upload debris tags to GreenHalo for City staff review.

#### **PRIOR TO FINAL OF BUILDING PERMIT**

- SW7. **Weight Tickets.** Prior to obtaining a Temporary or Final Certificate of Occupancy, individual weight tickets for all materials generated for discard or reuse by the project during demolition and construction activities shall be uploaded to Green Halo and submitted for review and approval by Environmental Services. At a minimum two (2) weeks review time is required.

## **SILICON VALLEY POWER**

### **GENERAL**

SVP1. Per correspondence with applicant 03/06/2026 “Re: 3000 Bowers PCC Comments”, this comment only applies if the project decides to request power over 2.5 MVA and move forward with SIS. Applicant does not plan to move forward with SIS at this time and understand the potential ramifications on the site plan/current design from the SIS.

**Interconnection Study.** This study would need to be completed prior to PCC Deemed Cleared. This study will assess the following:

- a. System capacity of SVP’s electric transmission and distribution systems to serve customer load.
  - b. System capacity of PG&E’s electric transmission system to serve customer load.
  - c. This is determined by studies performed by the California Independent System Operator (CAISO) in its yearly Transmission Planning Process (TPP).
  - d. Any mitigation measures identified, and/or construction schedules required by PG&E to serve customer load ramp will be communicated by SVP to the customer. Any PG&E identified mitigations and/or construction schedules are not controlled by SVP nor is SVP responsible for any delays caused by these project schedules.
  - e. Determine when to include customer load ramp in SVP’s load forecast to the California Energy Commission (CEC), provided that SVP determines, in sole discretion, that there is capacity available for the project.
  - f. Determine when the customer will be allowed to energize facilities, and allowed ramp schedule; provided that SVP determines, in sole discretion, that there is capacity available for the project.
  - g. Please see System Limitation Letter attached to SVP markups dated Nov. 10, 2022
  - h. These conditions of approval do not commit the City to (1) serve Developer’s electric load or (2) allocate any capacity to Developer. Further, any approval which this Project may receive from the City Council, Planning, or another City Department, shall not commit the city to (1) serve Developer’s electric load or (2) allocate any capacity to Developer.
- SVP2. **Applicant Design Process:** available to Applicants to expedite distribution electric substructure design.
- SVP3. **SVP Rules and Regulations:** Applicant shall comply with all applicable SVP rules, regulations, standards, guidelines, and requirements, as may be amended from time to time.
- SVP4. **SVP Equipment Clearances:**
- a. **Access Doors:** Ten (10) foot minimum clearance in front of equipment access doors.
  - b. **Pad Sides:** Five (5) foot minimum clearance from pad on sides without access doors.
  - c. **Truck Access:** Eighteen (18) foot minimum width on one side of the equipment pad for truck access.
  - d. **Barrier pipes:** (on sides accessible to vehicles)

- i. Thirty (30) inches from equipment sides.
- ii. Forty-Eight (48) inches in front of access doors. (use removable bollards)

**SVP5. SVP Conduit Clearances:**

- a. **Longitudinal:** Five (5) foot minimum between new conduits/piping and existing/proposed SVP conduits.
- b. **Vertical:** Twelve (12) inch minimum between new conduit/pipes perpendicular to existing SVP conduits.
- c. **Poles/Posts:** Three (3) foot six (6) inches clearance required from poles (electrolier, guy stub, service clearance, self-supporting steel, and light poles), except for riser conduits. This is reduced to a three (3) foot minimum for posts (signposts, barrier pipes, bollards, fence posts, and other similar posts).
- d. **Structures:** Five (5) foot minimum is required from walls, footings, retaining walls, landscape planter, or similar permanent structures.
- e. **Subsurface Facilities:** Five (5) foot minimum from new splice boxes, pull boxes, manholes, vaults, or similar subsurface facilities.
- f. **Fire Hydrant:** Five (5) foot minimum from fire hydrant thrust block. (Extends 5 feet on either side of the hydrant in line with the radial water pipe connected to the hydrant).

**SVP6. SVP Vault/Manhole Clearances:**

- a. Ten (10) foot minimum between adjacent Vaults or Manholes.
- b. Three (3) foot minimum from face of curb. (bollards required for vaults).

**SVP7. SVP Guy Anchor Clearances:** Five (5) foot minimum clearance is required between the center of anchor line and any excavation area.

**SVP8. Tree Clearances:**

- a. **Conduits:** Five (5) foot minimum to tree root barrier or other subsurface wall or structure.
- b. **Equipment:** Five (5) foot minimum to tree root barrier. The tree canopy drip line cannot be over the SVP equipment.
- c. **Subsurface Facilities:** Five (5) foot minimum to any electric department facilities. Any existing trees in conflict will have to be removed.
- d. **Easements:** No trees shall be planted in SVP's U.G.E.E or P.U.E's.
- e. **Transformer & Switch Placement:** these devices and pads may only be located outdoors. Clearances to buildings are defined in UG1225. All projects are to assume mineral oil fluid, unless otherwise approved by SVP.

**SVP9. SVP Standards.** Applicant shall comply with the following SVP standards (as may be amended or supplemented).

- a. UG1000 - Installation of Underground Substructures by Developers
- b. UG1250 – Encroachment Permit Clearances from Electric Facilities
- c. UG0339 – Remote Switch Pad
- d. OH1230 – Tree Clearances from Overhead Electric Lines
- e. SD1235 – Tree Planting Requirements Near Underground Electric Facilities
- f. UG1225 – Pad mounted Equipment Clearances and Protection
- g. UG0250 – High Density Residential Metering Requirements
- h. FO-1901 – Fiber Optic Splicing and Testing Methods
- i. SVP Rules and Regulations – Latest Edition

- SVP10. **SVP Standards, Miscellaneous:**
- a. No splice boxes are allowed between the SVP utility connection point and the applicants main switch board.
  - b. SVP does not utilize any sub-surface (below grade) devices in its system. This includes transformers, switches, etc.
- SVP11. **Meter Locations:**
- a. All interior meter rooms at ground level are to have direct, outside access through only ONE door. Interior electric rooms must be enclosed in a dedicated electric room and cannot be in an open warehouse or office space
- SVP12. **Underground Service Entrance**
- a. 277/480V Service or Lower) Underground service entrance conduits and conductors shall be “privately” owned, maintained, and installed per City Building Inspection Division Codes to the SVP defined utility connection point.
  - b. No cross-parcel distribution is allowed. SVP service points must be within the parcels that they serve.
- SVP13. **Code Sections:**
- a. The Applicant shall provide and install electric facilities per Santa Clara City Code chapter **17.15.210**.
  - b. Installation of underground facilities shall be in accordance with City of Santa Clara Electric Department standard UG-1000, latest version, and Santa Clara City Code chapter **17.15.050**.
  - c. The applicant shall perform, in accordance with current City standards and specifications, all trenching, backfill, resurfacing, landscaping, conduit, junction boxes, vaults, street light foundations, equipment pads and subsurface housings required for power distribution, street lighting, and signal communication systems, as required by the City in the development of frontage and on-site property. Upon completion of improvements satisfactory to the City, the Applicant will dedicate the improvement to the City subject to City’s acceptance the work. The applicant shall further install at his cost the service facilities, consisting of service wires, cables, conductors, and associated equipment necessary to connect a applicant to the electrical supply system of and by the City. After completion of the facilities installed by the Applicant, the City shall furnish and install all cable, switches, street lighting poles, luminaries, transformers, meters, and other equipment that it deems necessary for the betterment of the system per Santa Clara City Code chapter **17.15.210 (2)**.
- SVP14. **Existing Facilities:**
- a. All existing SVP facilities, onsite or offsite, are to remain unless specifically addressed by SVP personnel in a separate document. It is the Applicants responsibility to maintain all clearances from equipment and easements. The Applicant may contact SVP outside of the PCC process for clear definitions of these clearance requirements. Applicant should not assume that SVP will be removing any existing facilities without detailed design drawings from SVP indicating potential removals. Simply indicating that SVP facilities are to be removed or relocated on conceptual plans does not imply that this action has been approved by SVP.
  - b. Any relocation of existing electric facilities shall be at Applicants expense.

SVP15. **Generators:** Non-Utility Generator equipment shall not operate in parallel with the electric utility, unless approved and reviewed by the Electric Engineering Division. All switching operations shall be “Open-Transition-Mode”, unless specifically authorized by SVP Electric Engineering Division. A Generating Facility Interconnection Application must be submitted with building permit plans. Review process may take several months depending on size and type of generator. No interconnection of a generation facility with SVP is allowed without written authorization from SVP Electric Engineering Division.

#### **DESIGN / PERFORMANCE– PRIOR TO BUILDING PERMIT ISSUANCE**

SVP16. **Initial Information:** Applicant shall provide a site plan showing all existing utilities, structures, easements, and trees. The applicant shall also include a detailed panel schedule showing all current and proposed electric loads.

SVP17. **SVP Developers Work Drawing:** Applicant shall have a developers work drawing created for the site by either an SVP estimator or through the applicant design process. All SVP standards and clearance requirements as defined in the General Section of the COA’s must be met, or variance approvals must be granted by SVP. The developers’ work drawing shall include but is not limited to: SVP substructure for primary, low voltage, streetlight, and fiber facilities. SVP facilities may extend off-site to the nearest utility connection point to tie-in with existing infrastructure as deemed necessary by SVP.

SVP18. **Encroachment Permit:** Prior to issuance of Building Permits, the applicant shall submit an encroachment permit application with an **approved** SVP Developers Work Drawing for construction of electric utilities that comply with the latest edition of SVP Standards and Rules and Regulations, Electric Notes, and Electric Standard Details and Specifications.

SVP19. **Applicants Switchgear:** All applicant main switchgear with SVP meters must meet EUSERC standards and be approved by SVP’s meter shop prior to ordering. Switchgear for 12KV gear must have batteries sized for 4 hours of operation, no capacitive tripping, and 2 sets of relays, CTs, & PTs for each main. All double ended switchgear with a tie breaker, must include a kirk-key interlock scheme and an SVP provided warning label for the operation of the main tiebreaker.

#### **DURING CONSTRUCTION – PRIOR TO OCCUPANCY**

SVP20. **Easements:** Prior to the City’s issuance of Building or Grading Permits, the applicant shall provide a dedicated underground electric utility easement (U.G.E.E) around the electric onsite facilities (Not a P.U.E). The electric utility easement shall be a minimum of 10 feet wide around conduit and 5’ minimum around equipment and vault/manhole pads. Additionally, the applicant shall submit plans defining existing easements so Electric Division can verify if there are any conflicts with new proposed easements or improvements. The Applicant shall grant to the City, without cost, all easements and/or right of way necessary for serving the property of the Applicant and for the installation of utilities (Santa Clara City Code chapter 17.15.110).

SVP21. **Applicants Switchgear:** Applicants’ switchgear will be inspected on site by SVP to ensure compliance with approved switchgear drawings. Electric meters and main disconnects shall be installed per Silicon Valley Power Standard MS-G7, Rev. 2.

SVP22. **Electric Facilities:** Prior to the City's issuance of Occupancy, the applicant shall construct all electric utilities per the approved SVP Developers Work Drawing. SVP will

inspect all electric utility installations and all other improvements encroaching on electric facilities.

SVP23. **Municipal Fees:** Prior to electric service energization, all applicable fees per the City of Santa Clara's Municipal Fee Schedule shall be paid by the applicant.

SVP24. **Costs & Expenses:** Unless expressly stated otherwise or covered by a fee to be paid by the applicant, applicant shall be responsible for all costs and expenses associated with fulfilling these conditions of approval.

#### **OPERATIONAL CONDITIONS – AFTER OCCUPANCY**

SVP25. **Access:** SVP will require 24-hour unobstructed access to all SVP equipment which includes: manholes, transformers, vaults, switches, meters, indoor electrical rooms with SVP owned equipment etc.

#### **WATER & SEWER DEPARTMENT**

##### **DESIGN/ PERFORMANCE – PRIOR TO BUILDING PERMIT ISSUANCE**

W1. **Recycled Water Ready.** All onsite plumbing for non-domestic water uses (e.g. irrigation, industrial processes, cooling, etc.) shall be designed for recycled water use and shall comply with all Recycled Water regulations.

W2. **Potable Water Main.** The applicant shall be required to replace the existing water main on Oakmead Village Court from the end of the cul-de-sac to Oakmead Village Drive or as determined by the Development Impact Analysis

W3. **Encroachment Permit.** Prior to issuance of Building Permits, the applicant shall submit an encroachment permit application and design plans for construction of water utilities that comply with the latest edition of the Water & Sewer Utilities Water Service and Use Rules and Regulations, Water System Notes, and Water Standard Details and Specifications. In addition, prior to the City's issuance of Occupancy, the applicant shall construct all public water utilities per the approved plans. The Water & Sewer Utilities will inspect all public water utility installations and all other improvements encroaching public water utilities.

W4. **Utility Design Plans.** Utility Design Plans shall indicate the pipe material and the size of existing water, recycled water and sewer main(s). The plans shall show the nearest existing fire hydrant and the two nearest existing water main line gate valves near the project area. The plans shall show meter and backflow configurations to scale and per City of Santa Clara Water & Sewer Utilities Standard Details. Note that all new water meters and backflow prevention devices shall be located behind the sidewalk in a landscape area. Fire hydrants should be located two feet behind monolithic sidewalk if sidewalk is present; two feet behind face of curb if no sidewalk is present, per City Std Detail 18. The plans shall provide the profile section details for utilities crossing water, sewer, or recycled water mains to ensure a 12" minimum vertical clearance is maintained.

W5. **Utility Separations.** Applicant shall adhere to and provide a note indicating that all horizontal and vertical clearances comply with State and local regulations. The applicant shall maintain a minimum 12" of vertical clearance at water service crossing with other utilities, and all required minimum horizontal clearances from water services: 10' from sanitary sewer utilities, 10' from recycled water utilities, 8' from storm drain utilities, 5' from fire and other water utilities, 3' from abandoned water services, 5' from gas and electric utilities, and 5' from the edge of the propose or existing driveway. For sanitary sewer, water, and recycled water utilities, the applicant shall maintain a minimum horizontal

- clearance of 10' from existing and proposed trees. If applicant installs tree root barriers, clearance from tree reduces to 5' (clearance must be from the edge of tree root barrier to edge of water facilities). No structures (fencing, foundation, biofiltration swales, etc.) allowed over sanitary sewer, potable water and/or recycled water utilities and easements.
- W6. **Separate Services.** Applicant shall submit plans showing proposed water, recycled water, sanitary sewer, and fire services connected to a public main in the public right-of-way to the satisfaction of the Director of Water & Sewer Utilities. Different types of water and recycled water use (domestic, irrigation, fire) shall be served by separate water services, each separately tapped at the water main. Tapping on existing fire service line(s) is prohibited. Approved backflow prevention device(s) are required on all potable water services.
- W7. **City Standard Meters and Backflows.** All proposed meters and backflows for all water services shall meet the current City of Santa Clara Water & Sewer Utilities Standard Details. Plans shall show meter and backflow configurations to scale.
- W8. **Existing Services.** The applicant must indicate the disposition of all existing water and sewer services and mains on the plans. If the existing services will not be used, then the applicant shall properly abandon these services to the main per Water & Sewer Utilities standards and install a new service to accommodate the water needs of the project. The applicant shall bear the cost of any relocation or abandonment of existing Water Department facilities required for project construction to the satisfaction of the Director of Water and Sewer Utilities.
- W9. **On-Site Storm Drain Treatment.** Prior to issuance of Building Permit, the applicant shall submit plans showing any onsite storm water treatment system. The plan shall include a section detail of the treatment system. No water, sewer, or recycled water facilities shall be located within 5-feet of any storm water treatment system.
- W10. **Water Usage.** Prior to the issuance of Building Permits, the applicant shall provide documentation of water usage so the Water Division can verify the appropriate size of all proposed water meters. Please note that if the existing water services are incapable of supplying the water needs to the site, the existing services shall be abandoned, and new separate dedicated water services shall be provided for each use (domestic and irrigation).
- W11. **Landscaping.** All the landscaping for the project shall comply with the California Water Conservation in Landscaping Act, Government Code Section 65591 et. seq. All plants shall be either California native or non-invasive, low water-using or moderate water-using plants. High water-using plants and nonfunctional turf are prohibited.
- W12. **Water Features.** Prior to issuance of Building Permits, the applicant shall submit plan details for all water features (including but not limited to fountains and ponds) designed to include provisions for operating the system without City potable water supply and capable of being physically disconnected from source of potable water supply during City declared water conservation periods, to the satisfaction of the Director of the Water & Sewer Utilities. Decorative water features may be permanently connected to the City's recycled water supply.
- W13. **Easements.** Prior to City's issuance of Building or Grading Permits, the applicant shall provide a dedicated water utility easement around the backflow prevention device onsite. The water utility easement for the water services and all other public water appurtenances shall be a minimum 15 feet wide and be adjacent to the public right-of-way without overlapping any public utility easement. Additionally, the applicant shall submit plans

defining existing easements so Water Division can verify if there are any conflicts with proposed easements and water utilities.

- W14. **Underground Fire Permit.** Prior to issuance of Building Permits, applicant shall submit an underground fire permit unless otherwise waived by the Fire Department. If fire flow information is needed, applicant shall coordinate with Water and Sewer Utilities Department, for fire flow information at (408)615-2000. A dedicated fire service line, with an approved backflow prevention device, shall be used for on-site fire hydrants. Fire service lines required for commercial and industrial use shall be sized appropriately per fire flow demand and code requirements.

#### **DURING CONSTRUCTION**

- W15. **City Standard Meters and Backflow Installation.** No meters or backflows shall be installed prior to establishment of water service account with the Municipal Services Division of the Finance Department. The applicant shall provide a copy of the account information to the Water and Sewer Utilities Department Inspector and Meter Shop prior to installation of any meter or backflow. All meters and backflows approved for installation shall be tested prior to use. Water service connections shall not be used prior to authorization by the Water and Sewer Utilities inspector.
- W16. **Construction Water.** This project shall use recycled water for all construction water needs for onsite and offsite construction.
- W17. **Water Shortage Response Actions.** Pursuant to the City of Santa Clara's Urban Water Management Plan, during times of drought or water shortage, the City implements water shortage response actions in accordance with the level of water shortage declared. All construction activities and all new irrigation connections are subject to the Water Shortage Response Actions in effect at the time of construction and connection of the irrigation service.

Water Shortage Response Actions for Stage 2 and higher include water use restrictions that limit the use of potable water such as:

- a. Prohibiting the installation of new potable water irrigation services. new irrigation connections, construction, and dust control.
- b. Restrict the use of potable water used for construction and dust control if recycled water is available.

This project is subject to all the requirements and restrictions of the Water Shortage Response Actions in place or adopted during the duration of the project. For more information, visit the City of Santa Clara Water & Sewer Utilities website at [www.santaclaraca.gov/waterconservation](http://www.santaclaraca.gov/waterconservation).

#### **PRIOR TO FINAL OF BUILDING PERMIT**

- W18. **Record Drawings.** Upon completion of construction and prior to the City's issuance of a Certificate of Occupancy, the applicant shall provide "as-built" drawings of the public water utility infrastructure prepared by a registered civil engineer to the satisfaction of the Director of Water & Sewer Utilities Department.
- W19. **Conditional Releases.** The applicant shall comply with all the requirements of any building permit conditional release requirements.

**KEY:**

G = General

P = Planning Division

BD = Building Division

H = Housing & Community Services Division

F = Fire Department

PR = Parks & Recreation Department

PD = Police Department

E = Engineering Division

Streets Division (Landscape, Solid Waste, and Stormwater)

L = Landscape

SW = Solid Waste

SVP = Silicon Valley Power

W = Water & Sewer Department

**ACKNOWLEDGEMENT AND ACCEPTANCE OF CONDITIONS OF APPROVAL**

*Permittee/Property Owner*

The undersigned agrees to each condition of approval and acknowledges and hereby agrees to use the project property on the terms and conditions set forth in this permit.

Signature: \_\_\_\_\_

Printed Name: \_\_\_\_\_

Relationship to Property: \_\_\_\_\_

Date: \_\_\_\_\_

Pursuant to Santa Clara City Code 18.128.100, the applicant shall return this document to the Department, properly signed and dated, within 30-days following the date of the Acknowledgement.