



COOMB INC.

AIA, LEED AP BD+C

Is 120, San Lose CA 6072

OB IT 96232026223

Intahligmail.com

matDesign.com

DROOT STATE OF THE SET OF THE SET

95050

0

ARA

S

ANT

ഗ







SITE PLAN NOTES

- 1. SITE PLANS SHOWN IN THESE DRAWINGS ARE FOR REFERENCE ONLY, AND DO NOT REPRESENT A COMPREHENSIVE SITE SURVEY.
- COMPREHENSIVE SITE SURVEY.

 2. CONTRACTOR SHALL FIELD VERIFY ALL CONDITIONS BEFORE START OF WORK, AND SHALL VERIFY LOCATIONS OF ALL UNDERGROUND UTILITIES PRIOR TO ANY EXCAVATION.

 3. CONTRACTOR SHALL CONFIRM PROPERTY BOUNDARIES AND REQUIRED SETBACKS PRIOR TO START OF WORK. THE OWNER SHALL PROVIDE A LICENSED SURVEY AND A TITLE REPORT AS MAY BE
- REQUIRED BY CITY BUILDING INSPECTOR.

 4. CONTRACTOR IS RESPONSIBLE FOR ANY TEMPORARY EARTH SHORING REQUIRED DURING CONSTRUCTION.
- CONSTRUCTION.

 5. TREE PROTECTION DURING CONSTRUCTION: PROVIDE NO LESS THAN 4 STAKES AROUND TREE, LOCATED AT THE DRIP LINE, JOINEO BY CHAIN-LINK FENCING ALL AROUND THE TREE.

 6. PROVIDE SLOPE OF 1/4" PER FOOT FOR FIRST 48" ANNAY FROM FOUNDATIONS AND LANDINGS. SLOPE GRADE ANNAY FROM NEIGHBORING LOTS. SEE CIVIL DRAWLINGS (BY OTHERS, IT REGUIRED) FOR SITE WORK, SLOPES, DRAINAGE ETC. ROOF DRAINAGE SHALL BE DIRECTED TO LANDSCAPED
- 7. CONTRACTOR SHALL FIELD-VERIFY THAT THE EXISTING SANITARY SEWER MAIN IS AT LEAST 4°0.
- 7. OUNHARATOR SHALL FIELD-VEHICY HAT I HE EXISING SANLIARY SEWHEN MAIN IS ALLEASI AS SANLIC COMPLY WITH WATER USAGE REQUIREMENTS. AUTOMATIC LANDSCAPE IRRIGATION CONTROLLERS INSTALLED AT TIME OF FINAL INSPECTION SHALL OPERATE VIA WEATHER OR SOIL MOISTURE SENSORS.
 9. SEE CALGREEN COMPLIANCE NOTES FOR ADDITIONAL REQUIREMENTS.

CABRILLO AVENUE

ON-SITE STORM WATER MANAGEMENT

- 1. NEW RAINWATER DOWNSPOUTS SHALL BE DISCONNECTED AND BUNGER DIRECTED TO A LANDSCAPE AREA. EXTEND DOWNSPOUTS AT LEAST THREE TO SIX FEET AWAY FROM THE BUILDING FOUNDATION WALL AND DIRECT FLOW AWAY FROM THE BUILDING.
 2. DOWNSPOUTS MAY DANT TO SPLASH BLOCKS OR COBBLESTORES THAT DIRECT WATER

- 2. DOWNSPOUTS MAY DRAIN TO SPLASH BLOCKS OR COBBLESTONES THAT DIRECT WATER AWAY FROM BUILDING
 3. THRU-CUBB DRAINS ARE NOT ALLOWED.
 4. CAP THE SWERR WHERE THE DOWNSPOUT ONCE CONNECTED TO PREVENT DEBRIS AND ANIMALS FROM ENTERING AND DOORS FROM ESCAPING.
 5. DO NOT INSTALL DOWN SPOUTS OVER DRIVE WAYS AND PAVED AREAS SO THAT IT DOES NOT FLOW INTO ROAD STORM WATER DRAINS.




20" TREE

PUBLIC TRANSPORT FOR ADU 0.5 MILE







DEMOLITION CALCULATIONS AND NOTES EXISTING EXTERIOR WALL LENGTH= 199'-10" EXTERIOR WALL BEING REMOVED= 133"-8"
PERCENTAGE OF EXTERIOR WALL REMOVED= 153'-1 1/2"/199'-10" X 100= 76.62%

EXISTING ROOF WILL BE DEMOLISHED


Check VB Date 3/27/2022 Scale AS NOTED **Job No.** 2021-6

A-1A

EXISTING ROOF PLAN

ALL <E> ROOF SLOPES ARE 5:12, UON


0



DEMO (EXTERIOR WALLS) REMOVE INTERIOR WALLS AND FIXTURES


EXISTING FLOOR PLAN AND DEMO






Date 3/27/2022 Scale AS NOTED

A-2A









Bhooma Inc.
Bhooma Inc.
ani Bahi, Asaoc. Ala, LEED AP BD+C
reso zarve na 18 se 20 an uose cA effiz
reso zarve na 18 se 20 azza ezza
E Mata varizett-pranticom
www.Bhooms.eegn.com

AHALYA AND SANKAR ADDITION AND FEMODEL WITH ADD WADD JADU 1982 GRAHAM LANE SANTA CLARA, CA 95050



Drawn	MCD	
Check	VB	
Date	3/27/2022	
Scale	AS NOTED	
Job No.	2021-6	

A-2B





- NOTES:

 1. GUTTER COVER TO BE MANUFACTURED BY 'FLO-FREE LEAF GUARD' OR EQUIVALENT.

 2. PROVIDE A MINIMUM OF 1" AIRSPACE BETWEEN INSULATION AND THE ROOF SHEATHING PER CRC SECTION R806.3
- 3. FASTENERS FOR THE ROOFING SHALL BE CORROSION RESISTANT IN ACCORDANCE WITH CRC R905.2.5
- PER CALGREEN CODE A4.407.2-ROOF DRAINAGE SYSTEM/ DOWN SPOUTS SHOULD DISCHARGE TO 5 FEET MINIMUM AWAY FROM FOUNDATION TO APPROVED DRAINAGE
- SYSTEM OR RELEASE IN LANDSCAPE AREA OR OTHERWISE PERVIOUS AREA.
 VENT PIPES TERMINATE @6" ABOVE RR % 12" FROM ANY VERTICAL SUFFACE. MIN &
 ABOVE OR 10" HORIZONTALLY FROM ANY OPENABLE SKYLIGHT, IF ANY
- PROVIDE FIRE BLOCKING TO CUT OFF ALL CONCEALED DRAFT OPENINGS (VERTICAL AND HORIZONTAL) TO FORM AN EFFECTIVE BARRIER BETWEEN STORIES, AND BETWEEN A TOP STORY AND THE ROOF SPACE, PER CRC R302.11 SEE DETAIL B FOR 1 HR FIRE RATED WALL AND EAVE
- 8. NO EAVE VENTS WHEN WALL IS <5' FROM PROPERTY LINE AND IS 1HR RTD







	Drawn	MCD
	Check	VB
	Date	3/27/2022
	Scale	AS NOTED
	Job No.	2021-6
Ш		

NEW ROOF PLAN

LOWER ROOF 5KYLIGHT

LOWER ROOF

NEW ROOF SLOPE 4:12 MATERIAL: MIN 30 YEARS ROOF SHINGLES

LOWER ROOF

A-5