

CONDITIONS OF APPROVAL

In addition to complying with all applicable codes, regulations, ordinances and resolutions, the following **conditions of approval** are recommended:

GENERAL

- G1. If relocation of an existing public facility becomes necessary due to a conflict with the developer's new improvements, then the cost of said relocation shall be borne by the developer.
- G2. Comply with all applicable codes, regulations, ordinances and resolutions.

ATTORNEY'S OFFICE

- A1. The Developer agrees to defend and indemnify and hold City, its officers, agents, employees, officials and representatives free and harmless from and against any and all claims, losses, damages, attorneys' fees, injuries, costs, and liabilities arising from any suit for damages or for equitable or injunctive relief which is filed by a third party against the City by reason of its approval of developer's project.

COMMUNITY DEVELOPMENT

- C1. Obtain required permits and inspections from the Building Official and comply with the conditions thereof. If this project involves land area of 1 acre or more, the developer shall file a Notice of Intent (NOI) with the State Water Resources Control Board prior to issuance of any building permit for grading, or construction; a copy of the NOI shall be sent to the City Building Inspection Division. A storm water pollution prevention plan is also required with the NOI.
- C2. Submit plans for final architectural review to the Architectural Committee and obtain architectural approval prior to issuance of building permits. Said plans to include, but not be limited to: site plans, floor plans, elevations, landscaping, trash enclosure details, lighting and signage. Landscaping installation shall meet City water conservation criteria in a manner acceptable to the Director of Community Development.
- C3. The project would not qualify for exemption under CEQA guidelines and shall require an initial study /mitigated negative declaration.
- C4. Project shall provide a 5' wide sidewalk and at least 5' wide landscaping strip along Martin Avenue surrounding the project site.
- C5. A Landscape plan showing the tree protection plan and a replacement plan for review and approval by the City prior to any demolition, grading or other earthwork in the vicinity of the existing trees on the site. Landscape plan to include type and size of proposed trees. Coordinate with the City Arborist for the type, location, installation and maintenance of large canopy street trees fronting the project site along the public right-of-way. Type and size of tree replacement on project site shall be at the direction of the City Arborist and require Planning Division review and approval. Installation of root barriers and super-soil may be required with the installation of trees where electric, water, and sewer utilities are in proximity.
- C6. Project site landscaping shall be maintained in good condition throughout the life of the Project and no trees shall be removed without City review and approval. Trees permitted by the City for removal shall be replaced at a 2:1 ratio with 24-inch box specimen tree, or equal alternative as approved by the Director of Community Development.
- C7. A complete landscape plan that includes, type, size and location of all plant species shall be required as part of architectural review of the project. Review and approval of the complete landscape plan, including water conservation calculations and irrigation plan shall be required prior to issuance of building permits. Installation of landscaping is required prior to occupancy permits.
- C8. Commercial, industrial, and multi-family residential buildings must have enclosures for solid waste and recycling containers. The size and shape of the enclosure(s) must be adequate to serve the estimated solid waste and recycling needs and size of the building(s) onsite, and should be designed and located

on the property so as to allow ease of access by collection vehicles. As a general rule, the size of the enclosure(s) for the recycling containers should be similar to the size of the trash enclosure(s) provided onsite. Roofed enclosures with masonry walls and solid metal gates are the preferred design. Any required enclosure fencing (trash area, utility equipment, etc.) if not see-thru, shall have a six (6) inch opening along the bottom for clear visibility. Any gates or access doors to these enclosures shall be locked.

- C9. The noise levels from the proposed use shall be within the maximum permissible limits in the Light Industrial (ML) zone per the City's Noise Ordinance.
- C10. The Final Storm Water Management Plan (SWMP) must be certified by a third-party consultant from SCVURPP's current list of qualified consultants. Five copies of the approval letter from the certified third-party review (wet stamped and signed) must be submitted prior to the issuance of grading or building permit.
- C11. Construction activity shall be limited to the hours of 7:00 a.m. to 6:00 p.m. weekdays and 9:00 a.m. to 6:00 p.m. Saturdays for projects within 300 feet of a residential use and shall not be allowed on recognized State and Federal holidays.
- C12. Prior to the issuance final occupancy, the applicant shall enter into Operations and Maintenance (O&M) agreement with the City. The project operator is responsible for the operations and maintenance of the SWMP and storm water BMPs consistent with the O&M agreement throughout the life of the project.
- C13. The Developer shall comply with the Mitigations Monitoring and Reporting Program that will be identified in the Lightstone Data Center Initial Study / Mitigated Negative Declaration and shall be incorporated in the Conditions of Approval for this project.
- C14. Developer is responsible for collection and pick-up of all trash and debris on-site and adjacent public right-of-way.
- C15. As directed by the Architecture Committee at the publicly noticed meeting on September 18, 2019, the Applicant shall work with staff to enhance the architecture of the proposed building.
- C16. As directed by the Planning Commission at the publicly noticed meeting on November 13, 2019, the Applicant will continue to work with the staff to enhance the elevations of the proposed building.

ENGINEERING

- E1. Obtain site clearance through Engineering Department prior to issuance of Building Permit. Site clearance will require payment of applicable development fees. Other requirements may be identified for compliance during the site clearance process. Contact Engineering Department at (408) 615-3000 for further information.
- E2. All work within the public right-of-way and/or public easement, which is to be performed by the Developer/Owner, the general contractor, and all subcontractors shall be included within a Single Encroachment Permit issued by the City Engineering Department. Issuance of the Encroachment Permit and payment of all appropriate fees shall be completed prior to commencement of work, and all work under the permit shall be completed prior to issuance of occupancy permit.
- E3. Submit public improvement plans prepared in accordance with City Engineering Department procedures which provide for the installation of public improvements. Plans shall be prepared by a Registered Civil Engineer and approved by the City Engineer prior to approval and recordation of final map and/or issuance of building permits.
- E4. Damaged curb, gutter, and sidewalk within the public right-of-way along property's frontage shall be repaired or replaced (to the nearest score mark) in a manner acceptable to the City Engineer or his designee. The extents of said repair or replacement within the property frontage shall be at the discretion of the City Engineer or his designee.
- E5. Developer shall provide a complete storm drain study for the 10-year and 100-year storm events. The grading plans shall include the overland release for the 100-year storm event and any localized flooding areas. System improvements, if needed, will be at developer's expense.
- E6. Unused sanitary sewer laterals shall be removed.

- E7. Developer shall verify that existing sanitary sewer lateral to be used shall be in good condition and complies with City standards.
- E8. All storm drain mains and laterals, sanitary sewer mains and laterals shall be outside the drip line of mature trees or 10' clear of the tree trunk whichever is greater.
- E9. Provide root barriers when the drip line of the mature trees covers the sidewalk. Root barriers for sidewalk protection shall be 16' long or extend to drip line of the mature tree, whichever is greater, and be 1.5' deep, and centered on trees. Root barriers for curb and gutter protection shall be 16' long or extend to drip line of the mature tree, whichever is greater, and be 2' deep, and centered on trees.
- E10. Obtain Council approval of a resolution ordering vacation of existing public easement(s) proposed to be abandoned, if any, through Engineering Department, and pay all appropriate fees, prior to start of construction.
- E11. Dedicate required on-site easements for any new public utilities by means of subdivision map or approved instrument at time of development.
- E12. Entire width of Martin Avenue along the property frontage shall be cape sealed with digouts.
- E13. All proposed sidewalk, walkway, and driveway(s), shall be per ADA compliant City standard.
- E14. Show and comply with City's driveway vision triangle requirements at proposed driveway. Visual obstructions over three feet in height will not be allowed within the driver's sight triangle near driveways and intersections in order to allow an unobstructed view of oncoming traffic. Contact Traffic Engineering at (408) 615-3000 for further information.
- E15. Provide a minimum 5' wide sidewalk along the property frontage.
- E16. Provide ADA walkways connecting the proposed buildings to public sidewalk.
- E17. All proposed driveways shall be City standard ST-8.
- E18. Provide on-site crane staging area for loading of mechanical unit(s).
- E19. All traffic signing, messages, and symbols shall be thermoplastic.
- E20. Unused driveways in the public right-of-way shall be replaced with City standard curb, gutter, and sidewalk per City Standard Detail ST-12.
- E21. Protect in place all street signs along project frontage.
- E22. Sliding gate and swing gate at both entrances shall be at a minimum 25 feet from back of walk.
- E23. On-street parking shall not be counted towards on-site parking requirements.
- E24. Provide trash pickup on-site.
- E25. For the current proposed site development, provide the following minimum bicycle parking spaces at the main entrance and/or high visible area: 10 Class I bicycle spaces and 4 Class II bicycle spaces

ELECTRICAL

- EL1. Prior to submitting any project for Electric Department review, applicant shall provide a site plan showing all existing utilities, structures, easements and trees. Applicant shall also include a "Load Survey" form showing all current and proposed electric loads. A new customer with a load of 500KVA or greater or 100 residential units will have to fill out a "Service Investigation Form" and submit this form to the Electric Planning Department for review by the Electric Planning Engineer. Silicon Valley Power will do exact design of required substructures after plans are submitted for building permits.
- EL2. The Developer shall provide and install electric facilities per Santa Clara City Code chapter 17.15.210.
- EL3. Electric service shall be underground. See Electric Department Rules and Regulations for available services.
- EL4. Installation of underground facilities shall be in accordance with City of Santa Clara Electric Department standard UG-1000, latest version, and Santa Clara City Code chapter 17.15.050.
- EL5. Underground service entrance conduits and conductors shall be "privately" owned, maintained, and installed per City Building Inspection Division Codes. Electric meters and main disconnects shall be installed per Silicon Valley Power Standard MS-G7, Rev. 2.

- EL6. The developer shall grant to the City, without cost, all easements and/or right of way necessary for serving the property of the developer and for the installation of utilities (Santa Clara City Code chapter 17.15.110).
- EL7. If the “legal description” (not “marketing description”) of the units is condominium or apartment, then all electric meters and services disconnects shall be grouped at one location, outside of the building or in a utility room accessible directly from the outside. If they are townhomes or single-family residences, then each unit shall have it’s own meter, located on the structure. A double hasp locking arrangement shall be provided on the main switchboard door(s). Utility room door(s) shall have a double hasp locking arrangement or a lock box shall be provided. Utility room door(s) shall not be alarmed.
- EL8. If transformer pads are required, City Electric Department requires an area of 17’ x 16’-2”, which is clear of all utilities, trees, walls, etc. This area includes a 5’-0” area away from the actual transformer pad. This area in front of the transformer may be reduced from a 8’-0” apron to a 3’-0”, providing the apron is back of a 5’-0” min. wide sidewalk. Transformer pad must be a minimum of 10’-0 from all doors and windows, and shall be located next to a level, drivable area that will support a large crane or truck.
- EL9. All trees, existing and proposed, shall be a minimum of five (5) feet from any existing or proposed Electric Department facilities. Existing trees in conflict will have to be removed. Trees shall not be planted in PUE’s or electric easements.
- EL10. Any relocation of existing electric facilities shall be at Developer’s expense.
- EL11. Electric Load Increase fees may be applicable.
- EL12. The developer shall provide the City, in accordance with current City standards and specifications, all trenching, backfill, resurfacing, landscaping, conduit, junction boxes, vaults, street light foundations, equipment pads and subsurface housings required for power distribution, street lighting, and signal communication systems, as required by the City in the development of frontage and on-site property. Upon completion of improvements satisfactory to the City, the City shall accept the work. Developer shall further install at his cost the service facilities, consisting of service wires, cables, conductors, and associated equipment necessary to connect a customer to the electrical supply system of and by the City. After completion of the facilities installed by developer, the City shall furnish and install all cable, switches, street lighting poles, luminaries, transformers, meters, and other equipment that it deems necessary for the betterment of the system (Santa Clara City Code chapter 17.15.210 (2)).
- EL13. Electrical improvements (including underground electrical conduits along frontage of properties) may be required if any single non-residential private improvement valued at \$200,000 or more or any series of non-residential private improvements made within a three-year period valued at \$200,000 or more (Santa Clara City Code Title 17 Appendix A (Table III)).
- EL14. Non-Utility Generator equipment shall not operate in parallel with the electric utility, unless approved and reviewed by the Electric Engineering Division. All switching operations shall be “Open-Transition-Mode”, unless specifically authorized by SVP Electric Engineering Division. A Generating Facility Interconnection Application must be submitted with building permit plans. Review process may take several months depending on size and type of generator. No interconnection of a generation facility with SVP is allowed without written authorization from SVP Electric Engineering Division.
- EL15. Encroachment permits will not be signed off by Silicon Valley Power until Developers Work substructure construction drawing has been completed.
- EL16. All SVP-owned equipment is to be covered by an Underground Electric Easement (U.G.E.E.) This is different than a PUE. Only publically-owned dry utilities can be in a UGEE. Other facilities can be in a joint trench configuration with SVP, separated by a 1’ clearance, providing that they are constructed simultaneously with SVP facilities. See UG 1000 for details.
- EL17. Proper clearance must be maintained from all SVP facilities, including a 5’ clearance from the outer wall of all conduits. This is in addition to any UGEE specified for the facilities. Contact SVP before making assumptions on any clearances for electric facilities.

- EL18. Transformers and Switch devices can only be located outdoors. These devices MAY be placed 5' from an outside building wall, provided that the building wall in that area meets specific requirements. (See UG 1000 document for specifics) EXAMPLE: If there are any doors, windows, vents, overhangs or other wall openings within 5' of the transformer, on either side, then the transformer MUST be 10' or more away from the building. These clearances are to be assumed to be clear horizontally 5' in either direction and vertically to the sky.
- EL19. All existing SVP facilities, onsite or offsite, are to remain unless specifically addressed by SVP personnel by separate document. It is the Developers responsibility to maintain all clearances from equipment and easements. Developer to contact SVP outside of the PCC process for clear definitions of these clearance requirements. Developer should not assume that SVP will be removing any existing facilities without detailed design drawings from SVP indicating potential removals. *Simply indicating that SVP facilities are to be removed or relocated on conceptual plans does not imply that this action has been approved by SVP.*
- EL20. SVP does not utilize any sub-surface (below grade) devices in it's system. This includes transformers, switches, etc.
- EL21. All interior meter rooms are to have direct, outside access through only ONE door. Interior electric rooms must be enclosed in a dedicated electric room and cannot be in an open warehouse or office space.
- EL22. In the case of podium-style construction, all SVP facilities and conduit systems must be located on solid ground (aka "real dirt"),and cannot be supported on parking garage ceilings or placed on top of structures.
- EL23. Applicant is advised to contact SVP (CSC Electric Department) to obtain specific design and utility requirements that are required for building permit review/approval submittal. Please provide a site plan to Leonard Buttitta at 408-615-6620 to facilitate plan review.

WATER

- W1. The Water & Sewer Utilities Department highly recommends installing two fire services from different sides of the property separated by a main valve for a looped system.
- W2. The applicant shall coordinate with Mike Vasquez, Water Compliance Manager, regarding recycled water use for irrigation. Mike may be reached at (408)-615-2006.
- W3. The applicant must indicate the disposition of all existing water and sewer services and mains on the plans. If the existing services will not be used, then the applicant shall properly abandon these services to the main per Water & Sewer Utilities standards and install a new service to accommodate the water needs of the project.
- W4. The applicant shall submit a composite utility plan showing all utilities (including proposed fiber/electrical) and landscaping (trees/shrubbery) so that the Water Department can verify conflicts for proposed water services. Note that all new water meters and backflow prevention devices shall be located behind the sidewalk in a landscape area or in the landscape strip behind the curb.
- W5. Applicant shall adhere to and provide a note indicating all horizontal and vertical clearances. The applicant shall maintain a minimum 12" of vertical clearance at water service crossing with other utilities, and all required minimum horizontal clearances from water services: 10' from sanitary sewer utilities, 10' from recycled water utilities, 8' from storm drain utilities, 5' from fire and other water utilities, 3' from abandoned water services, 5' from gas utilities, and 5' from the edge of the propose or existing driveway. For sanitary sewer, water, and recycled water utilities, the applicant shall maintain a minimum horizontal clearance of 10' from existing and proposed trees. If applicant installs tree root barriers, clearance from tree reduces to 5' (clearance must be from the edge of tree root barrier to edge of water facilities).
- W6. Applicant shall submit plans showing proposed water, sanitary sewer, and fire service connected to a public main in the public right-of-way to the satisfaction of the Director of Water & Sewer Utilities.

Different types of water use (domestic, irrigation, fire) shall be served by separate water services, each separately tapped at the water main. Tapping on existing fire service line(s) is prohibited.

- W7. No structures (fencing, foundation, biofiltration swales, etc.) allowed over sanitary sewer and/or water utilities and easements.
- W8. A dedicated fire service line, with an approved backflow prevention device, shall be used for on-site fire hydrants.
- W9. The applicant shall submit plans showing any onsite storm water treatment system. The plan shall include a section detail of the treatment system. No water, sewer, or recycled water facilities shall be located within 5-feet of any storm water treatment system.
- W10. Approved backflow prevention device(s) are required on all potable water services. The applicant shall submit plans showing the location of the approved backflow prevention device(s). Note that all new water meters and backflow prevention devices shall be located behind the sidewalk in a landscape area.
- W11. Approved reduced pressure detector assembly device(s) are required on all fire services. The applicant shall submit plans showing existing and proposed fire service upgraded with reduced pressure detector assembly device, as per city standard 17, to the satisfaction of the Director of Water & Sewer Utilities.
- W12. A fire service upgrade may be required if the existing fire service is below ground. Applicant's fire service upgrade shall adhere to the requirements in Water and Sewer Utilities Standard Detail No. 31.
- W13. The applicant shall bear the cost of any relocation or abandonment of existing Water Department facilities required for project construction to the satisfaction of the Director of Water and Sewer Utilities.
- W14. Applicant must clearly identify between public and private water mains, indicating which services and mains belong to public and private streets. No public mains should be shown on private property or streets.
- W15. There is an existing 12" potable water AC main along Martin Avenue. Any connection of new service and/or abandonment of existing service will require a new section of main at the point of connection.
- W16. Prior to the issuance of Building Permits, the applicant shall provide documentation of water usage so the Water Division can verify the appropriate size of all proposed water meters. Please note that if the existing water services are incapable of supplying the water needs to the site, the existing services shall be abandoned and new separate dedicated water services shall be provided for each use (domestic and irrigation).
- W17. Prior to issuance of Building Permits, the applicant shall provide the profile section details for utilities crossing water, sewer, or reclaimed water mains to ensure a 12" minimum vertical clearance is maintained.
- W18. The applicant must indicate the pipe material and the size of existing water and sewer main(s) on the plans.
- W19. If fire flow information is needed, applicant shall coordinate with Water and Sewer Utilities Department, for fire flow information at (408) 615-2000.
- W20. Fire hydrants should be located two feet behind monolithic sidewalk if sidewalk is present; two feet behind face of curb if no sidewalk is present, per City Std Detail 18.
- W21. Prior to issuance of Building Permits, the applicant shall submit design plans for construction of water utilities that comply with the latest edition of the Water & Sewer Utilities Water Service and Use Rules and Regulations, Water System Notes, and Water Standard Details and Specifications. In addition, prior to the City's issuance of Occupancy, the applicant shall construct all public water utilities per the approved plans. The Water & Sewer Utilities will inspect all public water utility installations and all other improvements encroaching public water utilities.
- W22. Prior to City's issuance of Building or Grading Permits, the applicant shall provide a dedicated water utility easement around the backflow prevention device onsite. The water utility easement for the water services and all other public water appurtenances shall be a minimum 15 feet wide and be adjacent to the public right-of-way without overlapping any public utility easement. Additionally, the applicant shall

submit plans defining existing easements so Water Division can verify if there are any conflicts with proposed easements and water utilities.

- W23. Upon completion of construction and prior to the City's issuance of a Certificate of Occupancy, the applicant shall provide "as-built" drawings of the on-site public water utility infrastructure prepared by a registered civil engineer to the satisfaction of the Director of Water & Sewer Utilities.

POLICE

- PD1. A Coded Entry System is required for police access to enclosed parking lots and gated communities. This can be accomplished with a coded key pad system or the Police Department Knox Box key system.

We understand security is a prime concern for the tenants of the project, which necessitates some sort of secure building and admittance process. By having either of these secure access systems for law enforcement, it will allow us to better respond to emergency situations should they arise in the development. Examples of these systems can be reviewed at the following projects:

- 2585 El Camino Real (Coded key pad access)
- 3555 Monroe Street (Knox box key access)

This is for the sliding entry gate into the private parking lot.

- PD2. The developer shall meet the City of Santa Clara's guidelines established for radio signal penetration, detailed in the Communications Department's Public Safety Radio System Building Penetration Guidelines. The intended use of telecommunications sites shall be clearly and accurately stated in the use permit. The signal, of whatever nature, of any communications facility or system, shall in no way whatsoever interfere with or affect any police communication or police communication system.

FIRE

- F1. Traffic calming devices are not permitted on any designated fire access roadway, unless approved by the Fire Prevention & Hazardous Materials Division.
- F2. All Fire Department Access roadways shall be recorded as an Emergency Vehicle Access Easement (EVAE) on the final map. No other instruments will be considered as substitutions such as P.U.E, Ingress/Egress easements and/or City Right-of-Ways.
- F3. Provisions shall be made for Emergency Responder Radio Coverage System (ERRCS) equipment and two-way communications systems for elevator landings/areas of refuge, including but not limited to pathway survivability in accordance with Santa Clara Emergency Responder Radio Coverage System Standard.
- F4. Trees or other obstructions shall not interfere with aerial ladder access.
- F5. Prior to issuance of a Building Permit, Steps 1 through 3 summarized below must be addressed during the planning phase of the project. The development projects Phase I and/or Phase II environmental documents will be the project guiding documents:
- a. Step 1 – Hazardous Materials Closure (HMCP): This is a permit is issued by the Santa Clara Fire Department, Fire Prevention & Hazardous Materials Division. Hazardous materials closure plans are required for businesses that used, handled or stored hazardous materials. While required prior to closing a business this is not always done by the business owner, and therefore should be part of the developer's due diligence. The hazardous materials closure plans demonstrate that hazardous materials which were stored, dispensed, handled or used in the facility/business are safely transported, disposed of or reused in a manner that eliminates any threat to public health and environment.
 - b. Step 2 – Site Mitigation: Site mitigation is the cleanup or management of chemical contaminants in soil, soil vapor or groundwater. The type and extent of contamination on site(s) governs which of the regulatory agencies noted below will supervise the cleanup.
 - Santa Clara Fire Department, Fire Prevention & Hazardous Materials Division (CUPA)
 - Department of Toxic Substances Control (DTSC)

- State Water Resources Control Board
 - Santa Clara County, Department of Environmental Health.
- c. Step 3 – Community Development, Building Division Demolition Application: For the majority of projects within the City of Santa Clara, Steps 1 and/or 2 described above need to be completed prior to proceeding to demolition application in order to avoid permit approval delays. The purpose of a demolition permit is to ensure that the parcel is clear of debris and other health hazard material (lead, asbestos, etc.) and that the utility connections have been plugged and sealed.”

STREETS

Solid Waste

- ST1. For projects that involve construction, demolition or renovation of 5,000 square feet or more, the applicant shall comply with City Code Section 8.25.285 and recycle or divert at least sixty five percent (65%) of materials generated for discard by the project during demolition and construction activities. No building, demolition, or site development permit shall be issued unless and until applicant has submitted a construction and demolition debris materials check-off list. Applicant shall create a Waste Management Plan and submit a Construction and Demolition Debris Recycling Report through the City’s online tracking tool at <http://santaclara.wastetracking.com/>.
- ST2. For projects that involve a Rezoning, the applicant shall contact the Public Works Department, Street Maintenance Division at (408) 615-3080 to verify if the property falls within the City’s exclusive franchise hauling area. If so, the applicant may be required to use the City’s exclusive franchise hauler and rate structure for solid waste services.
- ST3. The applicant shall review the a site plan showing all proposed locations of solid waste containers, enclosure locations, and street/alley widths to the Public Works Department, Street Maintenance Division. All plans shall comply with the City’s Development Guidelines for Solid Waste Services as specified by development type. Contact the Street Maintenance Division at Street@santaclaraca.gov or at (408) 615-3080 for more information.

Stormwater

- ST4. Prior to City’s issuance of Building or Grading Permits, the applicant shall develop a Final Stormwater Management Plan and update the [SCVURPPP C.3 Data Form](#).
- ST5. The Final Stormwater Management Plan and all associated calculations shall be reviewed and certified by a qualified 3rd party consultant from the SCVURPPP List of Qualified Consultants, and a 3rd party review letter shall be submitted with the Plan.
- ST6. For projects that disturb a land area of one acre or more, the applicant shall file a Notice of Intent (NOI) with the State Water Resources Control Board for coverage under the State Construction General Permit (Order No. 2009-0009-DWQ) prior to issuance of any building permit for grading or construction. A copy of the NOI shall be submitted to the City Building Inspection Division, along with a stormwater pollution prevention plan (SWPPP). Active projects covered under the Construction General Permit will be inspected by the City once per month during the wet season (October – April).
- ST7. The applicant shall incorporate Best Management Practices (BMPs) into construction plans and incorporate post-construction water runoff measures into project plans in accordance with the City’s Urban Runoff Pollution Prevention Program standards prior to the issuance of Building or Grading Permits. Proposed BMPs shall be submitted to and thereafter reviewed by the Planning Division and the Building Inspection Division for incorporation into construction drawings and specifications.
- ST8. During the construction phase, all stormwater control measures shall be inspected for conformance to approved plans by a qualified 3rd party consultant from the SCVURPPP List of Qualified Consultants, and a 3rd party inspection letter shall be submitted to the Public Works Department, Street Maintenance Division. Building occupancy will not be issued until all stormwater treatment measures have been adequately inspected. For more information contact Street Maintenance at (408) 615-3080.

- ST9. The property owner shall enter into an Inspection and Maintenance (I&M) Agreement with the City for all installed stormwater treatment measures in perpetuity. Applicants should contact Karin Hickey at (408) 615-3097 or KaHickey@santaclaraca.gov for assistance completing the Agreement. For more information and to download the most recent version of the I&M Agreement, visit the City's stormwater resources website at <http://santaclaraca.gov/stormwater>.
- ST10. Any site design measures used to reduce the size of stormwater treatment measures shall not be removed from the project without the corresponding resizing of the stormwater treatment measures and an amendment of the property's I&M Agreement.
- ST11. Developer shall install an appropriate stormwater pollution prevention message such as "No Dumping – Flows to Bay" on any storm drains located on private property.
- ST12. All outdoor equipment and materials storage areas shall be covered and/or bermed, or otherwise designed to limit the potential for runoff to contact pollutants.
- ST13. Wastewater generated by the installation, cleaning, treating, or washing of the surface of copper architectural features, including copper roofs, shall not be discharged to the City's storm drain system.

HOUSING & COMMUNITY SERVICES

- H1. This Project is subject to the Affordable Housing requirements which may be met through payment of an impact fee of \$2.00 per square foot. The estimated fees are calculated as follow: 79,396 sq ft (proposed) minus 31,088 sq ft (existing) = \$96,616. Applicant shall pay impact fees prior to the issuance of the occupancy certificate of the building.

LOCATION MAP PLN2019-13745

